



young Blocks & Rigging



PO Box 3522
Seattle, WA 98124
Phone: (800) 321-9090
Fax: (206) 682-6881

ROLLER BEARING UTILITY BLOCKS

Compact, Lightweight and adaptable to many uses requiring fast running lines. Features manganese steel sheaves, Timken bearings, alloy pins and steel sides. Available with swivel shackle (-S)

Model #	706	708	709
Block #	V407	V408	V409
Sheave Size (inches)	6 x 1 1/4	8 x 1 1/4	9 x 1 1/4
Line Size (inches)	1/2	1/2	5/8
Throat Width (inches)	4 1/4	5 1/2	5 1/2
Safe Working Load	4 tons	4 tons	4 tons
Weight	17 lbs	29 lbs	33 lbs



LIGHTWEIGHT HEAVY DUTY HAULBACK BLOCKS

Features high-strength alloy steel sides and sheaves mounted on Timken tapered roller bearings for long service and are relatively light weight. Equipped with line guards.



Model #	1169	1369	1568	1569	1769a
Block #	V1033	V1034	V5749	V1035	V6041
Sheave Size (in)	11 x 2 1/2	13 x 2 1/2	15 x 2 1/2	15 x 2 1/2	17 x 2 1/2
Line Size (in)	3/4 - 7/8	3/4 - 7/8	3/4	7/8 - 1	1 - 1 1/8
Throat Height (in)	7 7/8	7 7/8	7 7/8	7 7/8	8 1/4
Throat Width (in)	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4
Safe Working Load	15 tons	15 tons	15 tons	15 tons	20 tons
Weight	62 lbs	66 lbs	78 lbs	78 lbs	104 lbs

LIGHT DUTY HAULBACK BLOCKS

Designed for fast-running small lines on light-duty haulback service. Sealed Timken bearings permit operation over long periods with little attention to lubrication. Features manganese sheaves, alloy steel pins and shackle. Equipped with line guards.

Model #	7081	7010
Block #	V464	V461
Sheave Size (inches)	8 x 1 1/2	10 x 1 3/4
Line Size (inches)	1/2	5/8
Throat Height (inches)	5 3/8	6 1/2
Throat Width (inches)	2 3/4	2 7/8
Safe Working Load	4 tons	4 tons
Weight	25 lbs	36 lbs




sales@youngcorp.com
www.youngcorp.com

Quality since 1902

WIDE SHEAVE BLOCKS


Heavy-duty blocks with extra-large throat opening. Adaptable to many uses requiring fast running lines and heavy loading. Equipped with manganese sheaves mounted on Timken bearings. Steel sides, alloy steel pins and shackles.

Model #	511
Block #	V390
Sheave Size (inches)	10 X 5
Line Size (inches)	1
Throat Height (inches)	7 1/2
Throat Width (inches)	6 3/4
Safe Working Load	22 tons
Weight	105 lbs



ROLLER BEARING RIGGER BLOCKS

Especially adapted for climbers' use, with a wide, long throat to pass splices. Features roller bearings, manganese sheaves, alloy pins, and steel sides with tailhold. Available with swivel shackle (-S).




Model #	806
Block #	V411
Sheave Size (in)	6 X 1 1/4
Line Size (inches)	1/2
Throat Height (inches)	5 3/8
Throat Width (inches)	2 3/8
Safe Working Load	4 tons
Weight with plain shackle	20 lbs

RIG UP BLOCKS

Designed for riggers use or as a utility block where a wide throat is required for passing eye splices and rigging. Extra-wide, alloy steel sheave is equipped with oversized Timken tapered roller bearings for long service life. Full-sided block sides protect the sheave and are strengthened with a tail bolt.

Model #	36	38
Block #	V6499	V6550
Sheave Size (inches)	3 x 6	3 x 8
Line Size (inches)	1/2	5/8
Throat Height (inches)	6	6
Throat Width (inches)	4	4
Safe Working Load	8 tons	8 tons
Weight	29 lbs	37 lbs



BRONZE BUSHED RIGGERS BLOCKS

For intermittent use. Well-adapted for riggers' service, due to ample throat clearance. Manganese sheaves, large bronze bushings and steel sides with tail holds are provided.

Model #	64
Block #	V363
Sheave Size (inches)	4 X 1
Line Size (inches)	3/8
Throat Height (inches)	3 1/4
Throat Width (inches)	2 1/2
Safe Working Load	4 tons
Weight	8 lbs

